









## Actuadores de Corrente

PM	LC	LM	EM	OM	FM1	CM	FM5
							
Tensão, Intensidade							
24 Vdc 0,5 A	24 Vdc 0,65 A	24 Vdc 0,5 a 1 A	24 Vdc 0,8 A	24 Vdc 0,8 A	24 Vdc 0,7 a 1 A	24 Vdc 1,5 A	24 Vdc 1,6 a 2 A
		230 Vac 0,15 A	230 Vac 0,225 A	230 Vac 0,225 A	230 Vac 0,23 A		
Forças (N)							
150	80 a 200	80 a 200	100 a 300	200 a 300	300 a 450	600	300 a 700
Cursos (mm)							
140 180	120 200 250 300 350 400 500	120 200 250 300 350 400 500	189 258 327 419 511 600 810	189 258 327 419 511 600 810	194 309 401	400 600 800	501 600 700
Versões disponíveis							
Solo	Solo	Solo Easydrive	Solo Tandem Twin Easydrive	Solo Twin Easydrive	Solo Tandem	Solo Tandem	Solo Tandem

Índice de Protecção: IP20.

Tandem: Versão com 2 motores sincronizados para chassis de grandes dimensões.

Twin: Versão com dois motores montados num só corpo - muito estético.

Easydrive: Sincronização simples de 2 a 8 motores.